

5 SIMPLE REASONS TO SWITCH

legrand



BELANKO™ / NEW RANGE OF WIRING DEVICES



 **legrand**®

5 IMPLRE REASONS TO SWITCH TO BELANKO™

With Belanko™, simplicity is beauty. Now, discover 5 good reasons why Belanko™ should be your choice for wiring devices.

| | |
|--------------------------|----|
| IDEAL CHO1CE | 02 |
| NEAT PRE2ENTATION | 04 |
| EASY & SAF3 INSTALLATION | 06 |
| MORE FUNCTION4LITIES | 08 |
| WIDE AS5ORTMENT | 12 |

IDEAL CHOICE



With Belanko™, switches perform exactly the way you expect them to. Beyond performance, we give you a choice between large rockers and the conventional small one.



It is your choice. Either go with the small rockers that hold 1 to 6 gangs, or the large rockers that feature 1 to 4 gangs.



FUNCTIONAL AND RELIABLE
1 gang switch with small rocker



COMPACT AND VERSATILE
5 gang switch with small rocker



CONTEMPORARY AND APPEALING
1 gang switch with large rocker



AESTHETICS MEETS FUNCTION
4 gang switch with large rocker

Colour Plates

Something more to go along with?



SUBTLE BEIGE
2 gang switch with large rocker and beige plate



DISTINCTIVE TAUPE
Double pole switch with red neon indicator and large rocker and taupe plate

NEAT PRE²ENTATION



We know how important it is for professionals like you to deliver perfect installations fast – always. Because your goal is also our goal, we ensure that our switches are always neatly wrapped with a soft protection film.



You now enjoy peace of mind. Your switch stays clean and neat until it is delivered to the customer.



The soft protection film keeps the product safe from dust.



Only the soft protection film will get stained by the ongoing wall paintwork.



The result is a perfectly neat installation – every time.


EASY & SAF³ INSTALLATION



Fitting switches is probably only one of the many tasks that you have to undertake. By making sure that installation is safe and easy, you are left with more time to tackle other tasks.




The safety features of Belanko™ wiring devices make installation both easy and safe.



Clear marking of terminals for easy identification and safe wiring



Double entry for each terminal facilitates wiring



Wires are held in place with the clamping plate. This reduces the risk of damaging wires. The combination of double entry and clamping plate ensures long term reliability of the connection.

Certified Quality

Your safety is our top priority. That's why Belanko™ wiring devices are compliant with safety standards.



MORE FUNCTION₄LITIES



Need something extra? Belanko™ has just that.
We provide additional functions to suggest just a few
more possibilities to meet your everyday lifestyle needs.



For enhanced comfort, Belanko™ offers dimming solutions for complex lighting.



1000W Dimmer




1500W Dimmer

1000W and 1500W Dimmers

These new 2-way Push ON/OFF Rotary dimmers can be associated with a switch for remote ON/OFF control from another point in the installation.

They memorise the last light level set before switch-off – and when switched on again, light level will be restored as previously memorised.



Voltage Selection (for 1500W dimmers)

A rated voltage converting switch on the upper right part of the base allows you to select – 230V or 127V. Factory setting is 230V.



MORE FUNCTION⁴LITIES

1500W dimmer Ideal for upgrade or retrofit

With the 1500W dimmer, upgrading of existing installations is really easy. It can be fitted in either 1 gang or 2 gang boxes, so that there is no need to change boxes in case of retrofit.



Safely connected to power – in different standards



13 A BS socket outlet, double pole, switched – whenever special safety is required



15 A US socket outlet, 2P + E



16 A German standard socket outlet, 2P + E

Socket protection IP44



The splash-proof cover for socket protection ensures IP44 with or without plug engaged.



Single TV socket, female

Get connected with TV, telephone and data sockets

Complete with TV, telephone and data sockets, Belanko™ not only keeps you connected to power but also to the rest of the world.



Double RJ 11 socket



Double RJ 45 socket

WIDE AS50RTMENT




Architrave,
1 gang, 1-way



5 gang switch



1 gang switch



4 gang switch



1500W Push ON/OFF
Rotary dimmer



Fan control



Single TV socket, "F" type




Double RJ 11 telephone
socket



Double RJ 45 data
socket




Push-button with bell symbol



45 A Double pole switch



1000W Push ON/OFF
Rotary dimmer



2 gang single pole BS switched socket outlet



1 gang BS switched
socket outlet



Fused connection unit



Cable outlet

PRODUCT CATALOGUE

NEW

Belanko™
single pole switches and push-buttons, small rocker

Belanko™
single pole switches and push-buttons, large rocker



617 100



617 108



617 115



617 000



617 006

Colour: White T084
Material: Thermoplastic with glossy finish
Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)
Supplied with 2 screws M3.5 for BS boxes

Colour: White T084
Material: Thermoplastic with glossy finish
Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)
Supplied with 2 screws M3.5 for BS boxes

| Pack | Cat.Nos | Single pole switches - small rocker |
|------|---------|---|
| | | Conform to BS EN 60669-1 and SASO No LIC 204803 |
| | | 10 AX - 250 V~ |
| 10 | 617 100 |  1 gang - 1-way switch |
| 10 | 617 101 |  1 gang - 2-way switch |
| 10 | 617 102 |  2 gang - 1-way switch |
| 10 | 617 103 |  2 gang - 2-way switch |
| 10 | 617 104 |  3 gang - 1-way switch |
| 10 | 617 105 |  3 gang - 2-way switch |
| 10 | 617 106 |  4 gang - 1-way switch |
| 10 | 617 107 |  4 gang - 2-way switch |
| 10 | 617 108 |  5 gang - 1-way switch |
| 5 | 617 110 |  6 gang - 1-way switch |
| 10 | 617 109 |  Intermediate switch |

| Pack | Cat.Nos | Single pole switches - large rocker |
|------|---------|--|
| | | Conform to BS EN 60669-1 and SASO No LIC 204803 |
| | | 10 AX - 250 V~ |
| 10 | 617 000 |  1 gang - 1-way switch |
| 10 | 617 001 |  1 gang - 2-way switch |
| 10 | 617 002 |  2 gang - 1-way switch |
| 10 | 617 003 |  2 gang - 2-way switch |
| 10 | 617 004 |  3 gang - 1-way switch |
| 10 | 617 005 |  3 gang - 2-way switch |
| 10 | 617 006 |  4 gang - 1-way switch |
| 10 | 617 007 |  4 gang - 2-way switch |
| 10 | 617 009 |  Intermediate switch |
| | | 20 AX - 250 V~ |
| 10 | 617 020 |  1 gang - 1-way |
| 10 | 617 021 |  1 gang - 2-way |
| 10 | 617 022 |  2 gang - 1-way |
| 10 | 617 023 |  2 gang - 2-way |

| Pack | Cat.Nos | Architrave |
|------|---------|--|
| 5 | 617 115 |  1 gang - 1-way |
| 5 | 617 116 |  Bell push |

| Pack | Cat.Nos | Push-button 4 A - 250 V~ |
|------|---------|---|
| | | Conform to BS EN 60669-1 and SASO No LIC 204803 |
| 10 | 617 111 |  Bell push |

| Pack | Cat.Nos | Push-button 4 A - 250 V~ |
|------|---------|--|
| | | Conform to BS EN 60669-1 and SASO No LIC 204803 |
| 10 | 617 011 |  Bell push |

Red catalogue numbers: New products

Belanko™
double pole switches and cooker control unit

Belanko™
dimmers and ventilation control



617 072



617 076



617 031




617 033

Colour: White T084
Material: Thermoplastic with glossy finish
Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)
Supplied with 2 screws M3.5 for BS boxes

Colour: White T084
Material: Thermoplastic with glossy finish
Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)
Supplied with 2 screws M3.5 for BS boxes


| Pack | Cat.Nos | Double pole switches |
|------|---------|--|
| | | Conform to BS EN 60669-1 |
| | | 20 A - 250 V~ |
| | | Conform to SASO No LIC 204803 |
| 10 | 617 070 |  1 gang - 1-way switch + red neon indicator |
| 10 | 617 071 |  1 gang - 1-way switch + red neon indicator + earth connection |
| 10 | 617 072 |  1 gang - 1-way switch + red neon indicator + earth connection with "Water Heater" marking |
| | | 32 A - 250 V~ |
| 10 | 617 074 |  1 gang - 1-way switch + red neon indicator, white rocker |
| | | 45 A - 250 V~ |
| | | Conform to SASO No LIC 204803 |
| 10 | 617 075 |  1 gang - 1-way switch |
| 10 | 617 076 |  1 gang - 1-way switch + red neon indicator |
| 5 | 617 077 |  2 gang - 1-way vertical switch + red neon indicator |

| Pack | Cat.Nos | Cooker Control Unit - 250 V |
|------|---------|---|
| | | Conform to SASO No LIC 204830 |
| 5 | 617 078 |  45 A DP switch + red neon and 13 BS switched socket outlet + red neon |


| Pack | Cat.Nos | Dimmers |
|------|---------|---|
| | | Conform to BS EN 60669-1 and SASO No LIC 204803 |
| 1 | 617 030 |  600 W - 230 V 50 Hz 1 gang - 1-way 86 x 86 mm Rotary on/off dimmer |
| 1 | 617 031 |  1000 W (230 V) - 500 W (127 V) 50/60 Hz 1 gang - 2-way 86 x 86 mm Push on/off and rotary dimmer |
| 1 | 617 032 |  1500 W (230 V) - 750 W (127 V) 50/60 Hz 2 gang - 2-way 86 x 146 mm Push on/off and rotary dimmer Can be mounted on 1 gang or 2 gang boxes |
| | | Ventilation control |
| | | Conform to BS EN 60669-1 and SASO No LIC 204803 |
| 1 | 617 033 |  Fan control 250 V~ 50 Hz |

Belanko™ dimmers

■ Fixing in 1 or 2 gang boxes - Dimmer Cat.No 617 032 - 1500 W



Preparation with 1-gang box




Preparation with 2-gang box

■ Choose your brightness adjustment - Dimmer Cat.Nos 617 031/032 - 1000 W / 1500 W


Push ON/OFF and rotary dimming




Push to turn ON



Rotate for brightness adjustment



Push to turn OFF
When pushed OFF, the dimmer memorizes the light level for the next switching ON




Push ON
The light level will be restored as previously memorized

Belanko™ ventilation control


■ Ventilation control Cat.No 617 033



Rotate to turn ON
When turned ON the fan control works at full capacity. This ensures that the whole ventilation system - fan included - is effectively ON.



Rotate to reduce the speed



Rotate to turn OFF
Going back to full capacity before turning OFF ensures that the whole ventilation system - and not only the fan - will be effectively switched OFF

Belanko™
television, telephone and data sockets



617 121



617 097



617 092



617 068

Colour: White T084
Material: Thermoplastic
Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)
Supplied with 2 screws M3.5 for BS boxes

Product for Singapore only

Product for Hong Kong only

| Pack | Cat.Nos | Television sockets |
|------|---------|-------------------------------------|
| | | Conform to SASO No LIC 204834 |
| 1 | 617 124 | 2 gang SCV outlet + TV-FM type F |
| 10 | 617 121 | Single TV socket, female |
| 10 | 617 120 | Single TV socket, "F" type |
| 10 | 617 123 | Double TV socket, female + "F" type |
| 10 | 617 122 | TV female pass through |
| 10 | 617 126 | TV female terminal |
| 10 | 617 125 | Double TV female terminal type |

| Pack | Cat.Nos | Data sockets |
|------|---------|-------------------------------|
| | | Conform to SASO No LIC 204834 |
| 10 | 617 090 | RJ 45 Cat.5e UTP |
| 10 | 617 091 | RJ 45 Cat.6 UTP |
| 10 | 617 092 | Double RJ 45 Cat.6 UTP |

| Pack | Cat.Nos | Shaver socket |
|------|---------|--|
| | | Conform to BS 61558 and SASO No LIC 204837 |
| 1 | 617 068 | 115/230 V - 20 VA - 50/60 Hz Surface or flush-mounting, back box to be min. 47 mm deep - 2 gang |

| Pack | Cat.Nos | Security switch |
|------|---------|--|
| 1 | 617 019 | 1 A resistive - 250 V~ Panic button |

| Pack | Cat.Nos | Telephone sockets |
|------|---------|--|
| | | Conform to SASO No LIC 204834 |
| 10 | 617 099 | Telephone connection block 10 connections |
| 10 | 617 095 | BT master |
| 10 | 617 096 | BT secondary |
| 10 | 617 097 | RJ 11 socket |
| 10 | 617 098 | Double RJ 11 socket |

NEW

Belanko™

socket outlets, fused connection units



617 041



617 046



617 065








617 081

Colour: White T084

Material: Thermoplastic with glossy finish

Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)

Supplied with 2 screws M3.5 for BS boxes

| Pack | Cat.Nos | British Standard socket outlets |
|------|---------|---|
| | | 13 A - 250 V~ Conform to BS 1363-2 and SASO No LIC 204830 |
| 10 | 617 040 |  1 gang unswitched |
| 5 | 617 045 |  2 gang unswitched |
| 10 | 617 041 |  1 gang single pole switched |
| 5 | 617 046 |  2 gang single pole switched |
| 10 | 617 042 |  1 gang single pole switched + neon |
| 5 | 617 047 |  2 gang single pole switched + neon |
| 10 | 617 141 |  1 gang single pole switched with external rocker |
| 5 | 617 146 |  2 gang single pole switched with inboard rockers |
| 5 | 617 049 |  2 gang single pole switched with red cover + neon |
| 10 | 617 043 |  1 gang double pole switched |
| 5 | 617 048 |  2 gang double pole switched |
| | | 15 A - 250 V~ Conform to BS 546 |
| 10 | 617 050 |  1 gang unswitched |
| 10 | 617 051 |  1 gang single pole switched |
| 10 | 617 052 |  1 gang single pole switched + neon |

| Pack | Cat.Nos | British Standard socket outlets (continued) |
|------|---------|--|
| | | 5 A - 250 V~ Conform to BS 546 |
| 10 | 617 054 |  1 gang single pole switched |
| | | Euro/US socket outlets - 10 A - 250 V~ / 15 A - 127 V~ |
| 10 | 617 060 |  1 gang - 2P |
| 10 | 617 061 |  1 gang - 2P + 10 AX switch |
| 10 | 617 062 |  1 gang - 2 x 2P |
| 10 | 617 063 |  1 gang - 2P+E |
| | | US socket outlet - 15 A - 127 V~ |
| 10 | 617 065 |  1 gang - 2P+E |
| | | German Standard socket outlet 16 A, 2P+E Shuttered with child protection |
| 10 | 617 066 |  1 gang |
| | | Fused connection units |
| | | 13 A Conform to BS 1363-4 and SASO No LIC 204803 |
| 10 | 617 080 |  Unswitched + cord outlet |
| 10 | 617 081 |  Switched + cord outlet |
| 10 | 617 082 |  Switched + neon + cord outlet |

Red catalogue numbers: New products

Belanko™
fused connection units (continued)
cable outlets, accessories, surface-mounting boxes



617 131 + 617 042



613 351

Belanko™
cover plates, blanking plates



617 151



617 155

Product for Hong Kong only

Fused connection units (continued)

| Pack | Cat.Nos | 2 A |
|------|-----------|-------------------------------|
| 10 | 617 080-2 | Unswitched + cord outlet |
| 10 | 617 081-2 | Switched + cord outlet |
| 10 | 617 082-2 | Switched + neon + cord outlet |

Cable outlets
Conform to BS 5733 and SASO No LIC 204840

| | | |
|----|---------|---------------|
| 10 | 617 085 | 20 A - 250 V~ |
| 10 | 617 086 | 45 A - 250 V~ |

Fixing accessories

| | | |
|-----|---------|--|
| 100 | 617 130 | Screw caps |
| 2 | 617 131 | Splash-proof cover Mainly for socket protection IP44 with or without plug engaged Space inside : 86 x 86 mm (for Belanko, Mallia and Synergy products) |

Surface-mounting boxes
Conform to BS 5733 and SASO No LIC 204803 depth 35 mm

| | | |
|----|---------|--|
| 10 | 613 349 | Architrave surface box |
| 8 | 613 350 | 1 gang surface box - 86 x 86 mm Supplied with earth terminal |
| 4 | 613 351 | 2 gang surface box - 86 x 146 mm Supplied with earth terminal |

Cover plates

| Pack | Cat.Nos | 1 gang |
|--------|---------|------------------|
| 5 | 617 150 | Horizontal beige |
| 5 | 617 151 | Vertical beige |
| 5 | 617 155 | Horizontal taupe |
| 5 | 617 156 | Vertical taupe |
| 2 gang | | |
| 5 | 617 152 | Horizontal beige |
| 5 | 617 153 | Vertical beige |
| 5 | 617 157 | Horizontal taupe |
| 5 | 617 158 | Vertical taupe |

Blanking plates
Conform to BS 5733 and SASO No LIC 204803

| | | |
|----|---------|--------|
| 10 | 617 128 | 1 gang |
| 5 | 617 129 | 2 gang |

